NSN 5930-00-102-0122

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-102-0122

Thread Class:
2b single pressure connection
Inside Diameter:
0.438 inches single connection
Overall Length:
5.312 inches
Overall Height:
2.875 inches
Overall Width:
5.581 inches
Body Length:
2.500 inches
Body Width:
4.625 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
5.250 inches
Pressure Switch Type:
Differential
Mounting Method:
Bracket and unthreaded hole
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
20.00 pounds per square inch
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
16.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.30 to 3.00 actuation point pounds per square inch and +0.30/+3.00 deactuation point pounds per square inch

NSN 5930-00-102-0122

Pressure Switch - Page 2 of 2

A048b0



Contact Adjustment Type:
External deactuation point screw and internal actuation point screw
Contact Voltage Rating In Volts:
115.0 dc at sea level second voltage
Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: