NSN 5930-00-102-0889

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-102-0889
Hazardous Locations/environmental Protection: Dustproof
Overall Height:
3.840 inches
Overall Width:
3.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
3.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.500 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Flange single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and metallic inclosure and cam actuated
Contact Voltage Rating In Volts:
115.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Cam Actuated Switch Contact Arrangement:
1 pole, double throw, both positions maintained single switch single section in-line
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section in-line
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Style Designator:
In-line, cam actuated

N/a

Shelf Life:

NSN 5930-00-102-0889 Rotary Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

Demilitarization:

No

Fiig:

A052b0