

View Online at <https://aerobasegroup.com/nsn/5930-00-102-6027>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

8.562 inches

Overall Height:

4.312 inches

Overall Width:

6.500 inches

Unthreaded Mounting Hole Diameter:

0.343 inches

Longest Horizontal Distance Between Mounting Centers:

5.125 inches

Longest Vertical Distance Between Mounting Centers:

5.125 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

7200.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

7.5 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+325.00/+3200.00 actuation point pounds per square inch gage and +240.00 to 3115.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0