NSN 5930-00-102-6029

Sensitive Switch - Page 1 of 2

Body Style: Hole mounted Overall Length: 1.940 inches



View Online at https://aerobasegroup.com/nsn/5930-00-102-6029

Center To Center Distance Between Mounting Facilities Parallel To Length:

| 1.000 inches |
|---|
| Overall Height: |
| 0.887 inches |
| Overall Width: |
| 0.687 inches |
| Body Length: |
| 1.940 inches |
| Body Width: |
| 0.687 inches |
| Body Height: |
| 0.840 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.094 inches |
| Actuator Height: |
| 0.045 inches |
| Actuator Free Position Height: |
| 0.625 inches |
| Maximum Voltage Rating In Volts: |
| 480.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 3.0 ounces |
| Switch Actuating Force: |
| 7.0 ounces |
| Actuator Movement: |
| Between 0.012 pretravel inches and 0.005 overtravel inches and 0.0007 differential inches |

NSN 5930-00-102-6029

Sensitive Switch - Page 2 of 2



| | Contact I | Load (| Current | Rating | At Max | imum F | Rated V | oltage: |
|--|-----------|--------|---------|--------|--------|--------|---------|---------|
|--|-----------|--------|---------|--------|--------|--------|---------|---------|

10.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0