

View Online at <https://aerobasegroup.com/nsn/5930-00-102-8252>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.469 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

3.375 inches

**First Flat Length:**

0.438 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.094 inches single actuator

**Overall Diameter:**

2.000 inches

**Nonturn Device Radius:**

0.375 inches at 3: 00 o'clock

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Pin at 3: 00 o'clock

**Switch Contact Basic Design:**

Pile-up

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

15.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0