## NSN 5930-00-103-1044

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-103-1044

Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.970 inches **Overall Height:** 1.000 inches **Overall Width:** 0.937 inches First Flat Length: 0.320 inches single actuator Flat Height: 0.218 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.750 inches single actuator **Nonturn Device Radius:** 0.375 inches at 3: 00 o'clock **Individual Section Quantity: Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 3rd section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Shaft Flat/slot Angular Location:** 20.0 degrees from nonturn device single actuator **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug

**Switch Actuator Positioning Increment:** 30.0 degrees single actuator

## NSN 5930-00-103-1044

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

0.2 amperes resistive load dc at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0