

View Online at <https://aerobasegroup.com/nsn/5930-00-103-1162>

Overall Length:

3.422 inches

Body Length:

Between 1.775 inches and 1.785 inches

Overall Diameter:

2.000 inches

Unthreaded Mounting Hole Diameter:

Between 0.198 inches and 0.203 inches

Distance Between Mounting Facility Centers:

Between 1.859 inches and 1.891 inches

Pressure Switch Type:

Absolute

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

3 pole, double throw, double break/double make, permanent jumper, one position momentary

Terminal Type:

Threaded stud

Contact Load Current Rating:

4.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+10.00 to 100.00 actuation point pounds per square inch absolute and -10.00/-5.00 deactuation point pounds per square inch absolute

Contact Adjustment Type:

External actuation point pointer and external deactuation point screw

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0