NSN 5930-00-103-3929

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-103-3929

| Overall Length: |
|---|
| 10.532 inches |
| Overall Height: |
| 3.750 inches |
| Overall Width: |
| 3.750 inches |
| Shaft Length: |
| 2.532 inches single actuator |
| Unthreaded Mounting Hole Diameter: |
| 0.213 inches single mounting facility |
| Individual Section Quantity: |
| 15 |
| Knob Manufacturer Code: |
| 82121 |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.297 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 2.297 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 2 each section front |
| Throw Quantity: |
| 4 each section rear |
| Mounting Method: |
| Bracket single mounting facility and unthreaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 125.0 dc at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 4 single actuator |
| Shaft Type: |
| Rectangular/square, threaded hole single actuator |
| Square Shaft Size: |
| 0.247 inches single actuator and 0.252 inches single actuator |
| Terminal Type: |
| Tab w/screw |
| Contact Switching Action: |

Breaks before makes each section rear

NSN 5930-00-103-3929 Rotary Switch - Page 2 of 2

A052b0



| Switch Actuator Positioning Increment: |
|--|
| 45.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Adjustable stop single actuator |
| Contact Load Current Rating: |
| 5.0 amperes resistive load dc at sea level |
| Special Features: |
| Accommodates one grey dial attached to black axtuator knob maximum diameter 3.750 in |
| Precious Material And Location: |
| Rotor and contact surfaces silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Tap, circuit selector |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |