

View Online at <https://aerobasegroup.com/nsn/5930-00-103-3958>

**Thread Class:**

3b single pressure connection

**Overall Length:**

4.250 inches

**Overall Width:**

3.625 inches

**Body Diameter:**

3.000 inches

**Distance Between Mounting Facility Centers:**

3.000 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

40.00 pounds per square inch gage

**Thread Size:**

0.562 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

450.0 milliamperes inductive load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point adjustable, preset

**Contact Adjustment Range:**

+0.40/+20.00 actuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

19.60 actuation point pounds per square inch gage and 16.00 deactuation point pounds per square inch gage and 4.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

440.0 ac at sea level first voltage

**Pressure Connector Type:**

Flare, threaded internal single connection

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Liquid

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A048b0