

View Online at <https://aerobasegroup.com/nsn/5930-00-103-3958>

Thread Class:

3b single pressure connection

Overall Length:

4.250 inches

Overall Width:

3.625 inches

Body Diameter:

3.000 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

40.00 pounds per square inch gage

Thread Size:

0.562 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

450.0 milliamperes inductive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable, preset

Contact Adjustment Range:

+0.40/+20.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

19.60 actuation point pounds per square inch gage and 16.00 deactuation point pounds per square inch gage and 4.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

440.0 ac at sea level first voltage

Pressure Connector Type:

Flare, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Liquid

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0