

View Online at <https://aerobasegroup.com/nsn/5930-00-103-5084>

**Hazardous Locations/environmental Protection:**

Dustproof

**Capillary Tube Length:**

36.0 inches

**Bulb Length:**

12.250 inches

**Bulb Diameter:**

0.188 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Bracket

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

30.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+100.00 to 450.00 actuation point degrees fahrenheit and +100.00 to 450.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point shaft and external actuation point shaft

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0