NSN 5930-00-103-5159

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-103-5159

| Body Style: |
|---|
| Bushing/hole mounted |
| Overall Length: |
| 1.940 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Overall Height: |
| 2.303 inches |
| Overall Width: |
| 0.687 inches |
| Bushing Length: |
| 0.938 inches |
| Body Length: |
| 1.940 inches |
| Body Width: |
| 0.687 inches |
| Body Height: |
| 0.990 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.139 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.250 inches |
| Actuator Height: |
| 0.375 inches |
| Actuator Free Position Height: |
| 1.313 inches |
| Maximum Voltage Rating In Volts: |
| 480.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |

Nonplie up Contact Arrangement.

1 pole, double throw, one position momentary single switch unit

NSN 5930-00-103-5159 Sensitive Switch - Page 2 of 2



| Switch Release Force: |
|--|
| 4.0 ounces |
| Switch Actuating Force: |
| Between 9.0 ounces and 13.0 ounces |
| Actuator Movement: |
| Between 0.015 pretravel inches and 0.140 overtravel inches and 0.002 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 250.000 milliamperes resistive dc and 15.000 amperes resistive ac |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 3 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |