# NSN 5930-00-104-0103

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-104-0103

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

3.437 inches

## **Overall Height:**

1.312 inches

## **Overall Width:**

1.188 inches

## First Flat Length:

0.375 inches single actuator

## Flat Height:

0.216 inches single actuator

## Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

0.875 inches single actuator

## Individual Section Quantity:

5

## **Operating Tempurature Range:**

-65.0 to 85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

1 each section rear

## **Throw Quantity:**

5 each section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

30.0 dc at sea level

## Shaft Flat/slot Angular Location:

315.0 degrees from nonturn device single actuator

## Switch Actuator Indexing Position Quantity:

5 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

# NSN 5930-00-104-0103

Rotary Switch - Page 2 of 2



**Contact Switching Action:** Breaks before makes each section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator **Detent Rotational Torque Range:** +1.000 to 8.000 inch-pounds single actuator **Contact Load Current Rating:** 70.0 milliamperes resistive load ac at altitude Style Designator: Tap, square frame **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0