

View Online at <https://aerobasegroup.com/nsn/5930-00-104-1442>

Thread Class:

3b all pressure connection

Overall Length:

5.400 inches

Overall Height:

2.970 inches

Overall Width:

4.020 inches

Unthreaded Mounting Hole Diameter:

0.221 inches

Longest Horizontal Distance Between Mounting Centers:

Between 4.680 inches and 4.720 inches

Longest Vertical Distance Between Mounting Centers:

Between 3.030 inches and 3.070 inches

Mounting Method:

Base and unthreaded hole

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

30.00 pounds per square inch

Thread Size:

0.437 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Sensing Element Burst Pressure:

50.00 pounds per square inch

Terminal Type:

Screw

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

1.065 actuation point pounds per square inch and 1.402 actuation point pounds per square inch and 0.288 differential point pounds per square inch and 0.337 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0