NSN 5930-00-104-1497

Rotary Switch Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-104-1497 **Overall Height:** 1.016 inches **Overall Width:** 0.953 inches **Body Thickness:** Between 0.060 inches and 0.065 inches **Unthreaded Mounting Hole Diameter:** 0.089 inches single mounting facility and 0.093 inches single mounting facility **Distance Between Mounting Facility Centers:** 0.812 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 2 single section front **Mounting Method:** Strut single mounting facility and unthreaded hole single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks, breaks before makes single section rear **Contact Load Current Rating:** 200.0 milliamperes inductive load dc at sea level and 20.0 milliamperes resistive load dc at sea level **Precious Material And Location:** Contact and rotor blade surfaces silver and contact and rotor blade surfaces gold **Precious Material:** Silver and gold **Style Designator:** Switch section, rotary Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A052b0