

View Online at <https://aerobasegroup.com/nsn/5930-00-105-1905>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Moisture proof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.750 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.570 inches

Actuator Roller Diameter:

0.187 inches

Actuator Roller Width:

0.109 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

7.0 ounces

Actuator Movement:

Between 0.219 pretravel inches and 0.030 overtravel inches and 0.025 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 250.000 milliamperes inductive dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0