

View Online at <https://aerobasegroup.com/nsn/5930-00-105-1905>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Moisture proof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.359 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Length:**

0.750 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.570 inches

**Actuator Roller Diameter:**

0.187 inches

**Actuator Roller Width:**

0.109 inches

**Maximum Voltage Rating In Volts:**

30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

7.0 ounces

**Actuator Movement:**

Between 0.219 pretravel inches and 0.030 overtravel inches and 0.025 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 250.000 milliamperes inductive dc

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0