NSN 5930-00-105-6630

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-105-6630

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Industrial use

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.876 inches

Body Width:

0.346 inches

Body Height:

0.600 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.062 inches

Actuator Free Position Height:

0.590 inches

Actuator Adapter Style:

Leaf

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

12.0 ounces

Actuator Movement:

Between 0.150 pretravel inches and 0.015 overtravel inches and 0.025 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

2 wire lead

NSN 5930-00-105-6630

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

