

View Online at <https://aerobasegroup.com/nsn/5930-00-105-6792>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.850 inches

Overall Height:

1.820 inches

Overall Width:

1.320 inches

Unthreaded Mounting Hole Diameter:

0.089 inches 1st mounting facility

Distance Between Mounting Facility Centers:

0.905 inches 1st mounting facility

Individual Section Quantity:

1

Operating Temperature Range:

-65.0 to 85.0 degrees celsius

Mounting Method:

Printed circuit 2nd mounting facility

Actuator Type:

Thumbwheel single actuator

Features Provided:

Illuminated

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 1st mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

2, 5, 10, 15, 20 single section

Contact Arrangement Truth Table:

Special, 3 pole - 10 positions single section

Special Features:

Stops provided to prevent use of positions 0 through 4

Color:

White single indicator marking

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0