

View Online at <https://aerobasegroup.com/nsn/5930-00-106-1972>

Hazardous Locations/environmental Protection:

Dustproof

Overall Height:

0.896 inches

Body Diameter:

0.970 inches

Mounting Slot Width:

0.176 inches

Body Height:

0.450 inches

End Application:

Stroposcatter radio terminal system antrc170. Landing craft air cushion (lcac), re Fridgeration systems. F-4 aircraft support equipment. Advanced air traffic control & landing system (atcals) 404l. 485l. F18-mpi air conditioner.

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Terminal Type:

Solder stud

Contact Load Current Rating:

37.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

90.00 actuation point degrees celsius and 61.00 deactuation point degrees celsius and 29.00 differential point degrees celsius

Contact Voltage Rating In Volts:

208.0 dc at sea level second voltage

Special Features:

Weapon system essential

Frequency In Hertz:

60.0 first voltage and 400.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0