

View Online at <https://aerobasegroup.com/nsn/5930-00-106-4999>

Thread Class:

2b single pressure connection

Inside Diameter:

0.250 inches single connection

Thread Length:

0.416 inches single pressure connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.343 inches

Overall Height:

4.562 inches

Overall Width:

3.500 inches

Body Length:

3.410 inches

Distance Between Mounting Facility Centers:

2.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.60 to 18.00 actuation point pounds per square inch gage and +0.40 to 17.80 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0