

View Online at <https://aerobasegroup.com/nsn/5930-00-106-7214>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 1.440 inches and 1.460 inches

Overall Height:

Between 1.173 inches and 1.183 inches

Overall Width:

1.380 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.990 inches single mounting facility and 1.010 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.168 inches single mounting facility and 1.188 inches single mounting facility

Mounting Method:

Flange single mounting facility and threaded hole single mounting facility

Actuator Type:

Thumbwheel single actuator

Features Provided:

Illuminated

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

Hud, radar, flyover, loran, tac I.L, tac mv, 1 ms.Hud, sins x.Y, z. Hdg, data single section

Contact Arrangement Truth Table:

Bcd, 1 pole - 10 positions single section

Color:

White single indicator marking

Style Designator:

Rectangular indicating

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0