

View Online at <https://aerobasegroup.com/nsn/5930-00-106-7232>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Corrosion proof and dustproof and explosion proof

**Overall Length:**

4.160 inches

**Overall Height:**

1.000 inches

**Overall Width:**

1.000 inches

**Body Diameter:**

1.000 inches

**Bushing Length:**

0.540 inches

**Body Length:**

2.600 inches

**Body Width:**

1.000 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.420 inches

**Actuator Height:**

1.020 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and out and down position locked in and out and center position locked in and out

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Holding solenoid

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc

**Special Features:**

Pull actuator out 0.090 in before changeing positions

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0