

View Online at <https://aerobasegroup.com/nsn/5930-00-106-7249>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

1.100 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Length:

4.500 inches

Actuator Style:

Leaf

Actuator Width:

0.093 inches

Actuator Free Position Height:

1.312 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

End Application:

Oliverperry class ffg, cimmaron class ao, ticonderoga class cg (47), wasp class lhd, mercy and comfort hospital ships class tah, wichita class aor, tarawa class lha, emory s. Land class as, kidd class ddg.

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

0.5 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

0.750 ounces

Actuator Movement:

Between 0.625 pretravel inches and 0.140 overtravel inches and 0.792 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0