

View Online at <https://aerobasegroup.com/nsn/5930-00-106-7249>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.940 inches

**Body Width:**

0.687 inches

**Body Height:**

1.100 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Length:**

4.500 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.093 inches

**Actuator Free Position Height:**

1.312 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**End Application:**

Oliverperry class ffg, cimmaron class ao, ticonderoga class cg (47), wasp class lhd, mercy and comfort hospital ships class tah, wichita class aor, tarawa class lha, emory s. Land class as, kidd class ddg.

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action single switch unit

**Switch Release Force:**

0.5 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

0.750 ounces

**Actuator Movement:**

Between 0.625 pretravel inches and 0.140 overtravel inches and 0.792 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0