## NSN 5930-00-106-7250



View Online at https://aerobasegroup.com/nsn/5930-00-106-7250

### Sensitive Switch - Page 1 of 2 **Body Style:** Hole mounted Hazardous Locations/environmental Protection: Dustproof Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches **Body Length:** 1.940 inches **Body Width:** 0.687 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches Actuator Length: 1.026 inches **Actuator Style:** Roller arm **Actuator Free Position Height:** 1.188 inches Actuator Roller Diameter: 0.370 inches **Actuator Roller Width:** 0.120 inches **Maximum Voltage Rating In Volts:** 250.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action single switch unit Switch Release Force: 0.25 ounces

#### Switch Actuating Force:

2.5 ounces

#### **Actuator Movement:**

Between 0.125 pretravel inches and 0.094 overtravel inches and 0.020 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive ac

#### **Terminal Type And Quantity:**

2 tab w/screw

#### Shelf Life:

N/a

# NSN 5930-00-106-7250

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

