

View Online at <https://aerobasegroup.com/nsn/5930-00-108-7019>

**Body Style:**

Bushing mount

**Bushing Length:**

0.469 inches

**Body Length:**

1.125 inches

**Body Width:**

0.625 inches

**Body Height:**

1.094 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

0.125 inches

**Actuator Height:**

0.688 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 10.000 amperes inductive dc and 4.000 amperes lamp dc and 16.000 amperes motor dc and 11.000 amperes resistive ac and 7.500 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes motor ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0