

View Online at <https://aerobasegroup.com/nsn/5930-00-108-8413>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Body Diameter:**

0.469 inches

**Bushing Length:**

0.281 inches

**Body Length:**

0.547 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.109 inches

**Actuator Height:**

0.328 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

**Special Features:**

Actuator has r. F. Interference shield

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0