

View Online at <https://aerobasegroup.com/nsn/5930-00-109-2875>

Thread Class:

3a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Height:

Between 1.740 inches and 1.760 inches

Overall Width:

Between 1.740 inches and 1.760 inches

Body Diameter:

1.812 inches

Bushing Length:

Between 0.474 inches and 0.494 inches

Body Length:

0.600 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.190 inches and 0.191 inches

Actuator Free Position Height:

0.739 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Helicopter, ch-53a/d/e, aircraft, ov-10a/h, helicopter, sof / hh-53h pave low, helicopter, super jolly h-53, engine, aircraft, t64-ge-3/7 (h-53b/c/h, hh-53b), helicopter, rh-53, helicopter, mh-53e

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

12

Thread Size:

1.063 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

16.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

64.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.062 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc

Special Features:

Weapon system essential

Thread Series Designator:

Un

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0