

View Online at <https://aerobasegroup.com/nsn/5930-00-109-5942>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

2.633 inches

**First Flat Length:**

0.438 inches 1st actuator

**Flat Height:**

0.218 inches 1st actuator

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

0.875 inches 1st actuator

**Overall Diameter:**

1.250 inches

**Nonturn Device Radius:**

0.531 inches at 5: 00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Pin at 5: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 3rd section rear

**Throw Quantity:**

7 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

7 1st actuator

**Shaft Type:**

Round, hollowed, flatted 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

500.0 milliamperes inductive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0