

View Online at <https://aerobasegroup.com/nsn/5930-00-109-9819>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Overall Length:**

1.890 inches

**Body Diameter:**

0.940 inches

**Bushing Length:**

0.440 inches

**Body Length:**

1.190 inches

**Overall Diameter:**

0.940 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thread Size:**

0.313 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 tab, solder lug

**Specification Data:**

81349-mil-s-22885/8 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0