## NSN 5930-00-110-0395



Rotary Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-110-0395 **Thread Class:** 2a single mounting facility **Overall Length: 4.187** inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.297 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 7 each section rear **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 600.0 highest ac voltage rating at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 7 single actuator **Terminal Type:** Screw **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

## NSN 5930-00-110-0395

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

4.0 amperes inductive load highest ac voltage rating at sea level

**Style Designator:** 

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0