

View Online at <https://aerobasegroup.com/nsn/5930-00-110-5534>

**Hazardous Locations/environmental Protection:**

Dustproof

**Body Diameter:**

Between 0.564 inches and 0.571 inches

**Distance Between Mounting Facility Centers:**

Between 0.808 inches and 0.816 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Flange

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

112.00 actuation point degrees fahrenheit and 92.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

30.0 dc at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0