NSN 5930-00-110-5534

Thermostatic Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-110-5534

Harardaya Lagatiana/anyiranmantal Brataction.
Hazardous Locations/environmental Protection:
Dustproof
Body Diameter:
Between 0.564 inches and 0.571 inches
Distance Between Mounting Facility Centers:
Between 0.808 inches and 0.816 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Flange
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
112.00 actuation point degrees fahrenheit and 92.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
30.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Disc w/flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A048b0