

View Online at <https://aerobasegroup.com/nsn/5930-00-110-5536>

Body Style:

Bushing mount

Overall Length:

Between 1.105 inches and 1.135 inches

Overall Height:

2.800 inches

Overall Width:

Between 0.605 inches and 0.635 inches

Bushing Length:

Between 0.455 inches and 0.485 inches

Body Length:

Between 1.105 inches and 1.135 inches

Body Width:

Between 0.605 inches and 0.635 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Height:

1.140 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

Between 1.145 inches and 1.175 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0