

View Online at <https://aerobasegroup.com/nsn/5930-00-110-5536>

**Body Style:**

Bushing mount

**Overall Length:**

Between 1.105 inches and 1.135 inches

**Overall Height:**

2.800 inches

**Overall Width:**

Between 0.605 inches and 0.635 inches

**Bushing Length:**

Between 0.455 inches and 0.485 inches

**Body Length:**

Between 1.105 inches and 1.135 inches

**Body Width:**

Between 0.605 inches and 0.635 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Height:**

1.140 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in and center position locked in

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

Between 1.145 inches and 1.175 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0