## NSN 5930-00-110-7650

Flow Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-110-7650

n	perating	Tom	nuratu	ro F	ating	٧.
u	beraunu	I EIII	puratu	пег	taunu	J.

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:** 

Threaded bushing and line

**Features Provided:** 

Hermetically sealed case

**Contact Action Stimulus:** 

Decrease

**Thread Size:** 

0.500 inches single threaded bushing

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally closed, momentary action

**Terminal Type:** 

Wire lead

**Contact Load Current Rating:** 

500.0 milliamperes resistive load second voltage

**Contact Adjustability:** 

Actuation point not adjustable

**Contact Stimulus Rating:** 

45.00 actuation point gallons per minute

**Contact Voltage Rating In Volts:** 

32.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Liquid

**Thread Series Designator:** 

Npt single threaded bushing

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0