NSN 5930-00-110-7676

Thermostatic Switch - Page 1 of 2

Thread Class:

to turn out of off position



View Online at https://aerobasegroup.com/nsn/5930-00-110-7676

2b all threaded hole
Overall Length:
2.953 inches
Overall Height:
1.656 inches
Overall Width:
2.485 inches
Capillary Tube Length:
18.0 inches
Bulb Length:
Between 14.875 inches and 16.875 inches
Bulb Diameter:
0.188 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket and threaded hole
Thready Qty Per Inch (tpi):
32 single threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.112 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained
Terminal Type:
Tab w/screw
Contact Load Current Rating:
27.0 amperes resistive load first voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+0.00/+800.00 actuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point shaft with scale
Contact Voltage Rating In Volts:
480.0 ac at sea level fourth voltage
Special Features:

Switch has dial with a rotation arc of 31o degrees which fits over flatted shaft 0.938 in. Lg, 0.250 in. Diameter requiring min 10 in. Oz torque

NSN 5930-00-110-7676

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas
Thread Series Designator:
Unc all threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0