

View Online at <https://aerobasegroup.com/nsn/5930-00-110-7700>

**Overall Length:**

5.250 inches

**Overall Height:**

5.250 inches

**Overall Width:**

2.781 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.438 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

0.812 inches

**Longest Vertical Distance Between Mounting Centers:**

3.312 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.469 inches single pressure connection

**Mounting Facility Pattern:**

Obtuse triangle

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

80.00 pounds per square inch

**Terminal Type:**

Screw

**Contact Load Current Rating:**

16.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+3.00 to 50.00 actuation point pounds per square inch and +3.00/+50.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0