

View Online at <https://aerobasegroup.com/nsn/5930-00-110-7700>

Overall Length:

5.250 inches

Overall Height:

5.250 inches

Overall Width:

2.781 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

2.438 inches

Intermediate Horizontal Distance Between Mounting Centers:

0.812 inches

Longest Vertical Distance Between Mounting Centers:

3.312 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.469 inches single pressure connection

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

80.00 pounds per square inch

Terminal Type:

Screw

Contact Load Current Rating:

16.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+3.00 to 50.00 actuation point pounds per square inch and +3.00/+50.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0