## NSN 5930-00-110-7700

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-110-7700

Overall Length:
5.250 inches
Overall Height:
5.250 inches
Overall Width:
2.781 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Longest Horizontal Distance Between Mounting Centers:
2.438 inches
Intermediate Horizontal Distance Between Mounting Centers:
0.812 inches
Longest Vertical Distance Between Mounting Centers:
3.312 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.469 inches single pressure connection
Mounting Facility Pattern:
Obtuse triangle
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Sensing Element Burst Pressure:
80.00 pounds per square inch
Terminal Type:
Screw
Contact Load Current Rating:
16.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+3.00 to 50.00 actuation point pounds per square inch and +3.00/+50.00 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:
115.0 ac at sea level single voltage

**Pressure Connector Type:** 

Plain, threaded internal single connection

## NSN 5930-00-110-7700

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular w/bracket
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0