

View Online at <https://aerobasegroup.com/nsn/5930-00-111-8619>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

2.700 inches

Overall Height:

1.270 inches

Overall Width:

1.270 inches

Body Diameter:

1.270 inches

Bushing Length:

0.850 inches

Body Length:

0.620 inches

Case Material:

Plastic

Actuator Diameter:

0.550 inches

Actuator Height:

0.470 inches

Maximum Voltage Rating In Volts:

24.0 dc

End Application:

Aircraft phantom f-4, hercules c-130, f-111, eagle f-15, thunderbolt ii a-10, awacs e-3a, f-16, helicopter super jolly h-53, vehicle aircraft refueler r-9, p-22 firetruck, tractor aircraft towing a/s32u-30, aircraft support equipment f-5, ov-10a, c-5, t-37, t-38, f-106, b-52; 4210-01-486-1035 tfft (tactical fire fighting truck); 2420-66-148-7692, hmee (high mobility engineer excavator)

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces and contactor silver

Thread Series Designator:

Un

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0