NSN 5930-00-112-4483

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-112-4483

Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.880 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.610 inches
Actuator Free Position Height:
1.312 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
End Application:
Support equipment, f-4 aircraft.
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
13.0 ounces
Actuator Movement:

Between 0.015 pretravel inches and 0.140 overtravel inches and 0.020 differential inches

NSN 5930-00-112-4483

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0