## NSN 5930-00-112-4607

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-112-4607

| view Online at https://aeiobasegroup.com/nsil/3930-00-112-4007  |  |
|---|--|
| Hazardous Locations/environmental Protection:   |  |
| Watertight  |  |
| Overall Length:   |  |
| 5.500 inches  |  |
| Overall Height:   |  |
| 8.250 inches  |  |
| Overall Width:  |  |
| 2.813 inches  |  |
| Body Height:  |  |
| 5.000 inches  |  |
| Longest Horizontal Distance Between Mounting Centers:   |  |
| 2.406 inches  |  |
| Shortest Horizontal Distance Between Mounting Centers:  |  |
| 1.203 inches  |  |
| Longest Vertical Distance Between Mounting Centers:   |  |
| 3.281 inches  |  |
| Tempurature Sensing Element Type:   |  |
| Bulb  |  |
| Mounting Method:  |  |
| Surface   |  |
| Contact Action Stimulus:  |  |
| Increase  |  |
| Mounting Facility Pattern:  |  |
| Isosceles triangle  |  |
| Terminal Type:  |  |
| Tab w/screw   |  |
| Contact Load Current Rating:  |  |
| 16.0 amperes resistive load second voltage  |  |
| Contact Adjustability:  |  |
| Deactuation point adjustable and actuation point adjustable   |  |
| Contact Adjustment Range:   |  |
| +90.00 to 165.00 actuation point degrees fahrenheit and +90.00/+165.00 deactuation point degrees fahrenheit |  |
| Contact Adjustment Type:  |  |
| External deactuation point screw and external actuation point screw   |  |
| Contact Voltage Rating In Volts:  |  |
| 115.0 dc at sea level second voltage  |  |
| Media For Which Designed:   |  |
| Gas   |  |
| Precious Material And Location:   |  |
| Contacts silver   |  |
| Precious Material:  |  |
| Silver  |  |
|   |  |

## NSN 5930-00-112-4607

Thermostatic Switch - Page 2 of 2

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

