NSN 5930-00-113-4952

Thermostatic Switch - Page 1 of 2

N/a



view Online at https://aerobasegroup.com/nsn/5930-00-113-4952
Hazardous Locations/environmental Protection:
Salt spray proof and vibration resistant and dustproof
Overall Length:
0.937 inches
Overall Height:
0.670 inches
Body Diameter:
0.640 inches
Mounting Slot Width:
0.127 inches
Distance Between Mounting Facility Centers:
0.750 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
125.0 degrees celsius and -65.0 degrees celsius
Mounting Method:
Bracket and slot
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
250.00 actuation point degrees fahrenheit and 220.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Disc w/flange
Shelf Life:

NSN 5930-00-113-4952

Thermostatic Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A048b0