

View Online at <https://aerobasegroup.com/nsn/5930-00-113-4952>

Hazardous Locations/environmental Protection:

Salt spray proof and vibration resistant and dustproof

Overall Length:

0.937 inches

Overall Height:

0.670 inches

Body Diameter:

0.640 inches

Mounting Slot Width:

0.127 inches

Distance Between Mounting Facility Centers:

0.750 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

125.0 degrees celsius and -65.0 degrees celsius

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

250.00 actuation point degrees fahrenheit and 220.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0