NSN 5930-00-114-4353

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-114-4353

Thread Class:	
---------------	--

3a single pressure connection

Thread Length:

0.550 inches single pressure connection

Overall Length:

3.250 inches

Outside Diameter:

0.438 inches single connection

Body Length:

1.550 inches

Overall Diameter:

1.000 inches

Unthreaded Mounting Hole Diameter:

0.173 inches

Distance Between Mounting Facility Centers:

0.700 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.680 inches

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

65.00 actuation point pounds per square inch gage and 50.00 deactuation point pounds per square inch gage

NSN 5930-00-114-4353

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 28.0 dc at altitude single voltage Pressure Connector Type: Flared, threaded external single connection Media For Which Designed: Gas Style Designator: Cylindrical Thread Series Designator: Unjf single pressure connection

-- Demilitarization:

Unit Of Measure:

Shelf Life:

N/a

Yes - demil/mli

Fiig:

A048b0