

View Online at <https://aerobasegroup.com/nsn/5930-00-114-4388>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.000 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.875 inches single actuator

Overall Diameter:

1.938 inches

Nonturn Device Radius:

0.500 inches at 5: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 5: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

Special Features:

One 0.082 in. Diameter hole through shaft

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0