NSN 5930-00-115-0024

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-115-0024

Thread Class: 2a single pressure connection **Thread Length:** 0.237 inches and 0.297 inches single pressure connection **Overall Length:** 2.815 inches **Overall Diameter:** 1.270 inches **Pressure Switch Type:** Absolute **Operating Tempurature Rating:** Between 28.0 degrees fahrenheit and 130.0 degrees fahrenheit **Mounting Method:** Clamp Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Thread Size:** 0.4375 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 3.0 amperes resistive load second voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 18.80 actuation point pounds per square inch absolute and 3.60 differential point pounds per square inch absolute **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage **Pressure Connector Type:** Flared, threaded external single connection Frequency In Hertz: 60.0 single voltage Media For Which Designed: Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

NSN 5930-00-115-0024

Pressure Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0