NSN 5930-00-115-7265

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-115-7265

| Overall Length: |
|--|
| 5.906 inches |
| Overall Height: |
| 4.562 inches |
| Overall Width: |
| 3.500 inches |
| Body Height: |
| 4.562 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 2.250 inches |
| Pressure Switch Type: |
| Differential |
| Width Across Flats: |
| 1.404 inches |
| Mounting Method: |
| Bracket |
| Thready Qty Per Inch (tpi): |
| 18 second pressure connection |
| Contact Action Stimulus: |
| Increase |
| Proof Pressure: |
| 10.00 pounds per square inch |
| Thread Size: |
| |
| 0.250 inches second pressure connection |
| 0.250 inches second pressure connection Nonpile-up Contact Arrangement: |
| |
| Nonpile-up Contact Arrangement: |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Adjustability: |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Adjustability: Deactuation point adjustable and actuation point adjustable |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +0.25/+3.00 actuation point pounds per square inch gage and +0.03 to 2.78 deactuation point pounds per square inch gage |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +0.25/+3.00 actuation point pounds per square inch gage and +0.03 to 2.78 deactuation point pounds per square inch gage Contact Adjustment Type: |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +0.25/+3.00 actuation point pounds per square inch gage and +0.03 to 2.78 deactuation point pounds per square inch gage Contact Adjustment Type: External deactuation point screw and external actuation point screw |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +0.25/+3.00 actuation point pounds per square inch gage and +0.03 to 2.78 deactuation point pounds per square inch gage Contact Adjustment Type: External deactuation point screw and external actuation point screw Frequency In Hertz: |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +0.25/+3.00 actuation point pounds per square inch gage and +0.03 to 2.78 deactuation point pounds per square inch gage Contact Adjustment Type: External deactuation point screw and external actuation point screw Frequency In Hertz: 60.0 single voltage |
| Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +0.25/+3.00 actuation point pounds per square inch gage and +0.03 to 2.78 deactuation point pounds per square inch gage Contact Adjustment Type: External deactuation point screw and external actuation point screw Frequency In Hertz: 60.0 single voltage Media For Which Designed: |

Npt second pressure connection

Thread Series Designator:

NSN 5930-00-115-7265

Pressure Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0